

*AMENDMENTS TO THE SPECIFICATION*

Replace paragraph [0059] with:

Thus, it is seen that the curve has the shape ~~left right~~ on the left of the resonance peak throughout the entire discharging area ratio from 0 to 1, and it has a negative slope and allows stable control.

At page 47, replace equation 8 with:

$$\begin{aligned}
 M &= \frac{V_p}{V_0} = \frac{1}{\sqrt{2}} \frac{\left(1 + \frac{C_p}{C_g}\right) \frac{V_p}{V^*} - 1}{1 - \left(1 + \frac{C_a}{C_g}\right) \frac{V^*}{V_p}} \\
 &= \frac{1}{\sqrt{2}} \frac{1 - \left(1 + \frac{C_a}{C_g}\right) \frac{\sqrt{2}V^*}{V_0}}{\left(1 + \frac{C_p}{C_g}\right) \frac{V_0}{\sqrt{2}V^*} - 1} \quad \dots(8)
 \end{aligned}$$

$$\begin{aligned}
 M &= \frac{V_p}{V_0} = \frac{1}{\sqrt{2}} \frac{\left(1 + \frac{C_p}{C_g}\right) \frac{V_p}{V^*} - 1}{1 - \left(1 + \frac{C_a}{C_g}\right) \frac{V^*}{V_p}} \\
 &= \frac{1}{\sqrt{2}} \frac{1 - \left(1 + \frac{C_a}{C_g}\right) \frac{\sqrt{2}V^*}{V_0}}{\left(1 + \frac{C_p}{C_g}\right) \frac{V_0}{\sqrt{2}V^*} - 1} \quad \dots(8)
 \end{aligned}$$

Replace paragraph [0252] with:

FIG. 20 also shows variations of the load voltage exhibited when the peak voltage V0 of the effective sine wave is varied, i.e., variations of the load peak voltage

V<sub>p</sub>, where the characteristic curves ~~S74 S81~~ and ~~S72 S82~~ show the variations respectively with C<sub>g</sub>/C<sub>a</sub>=1.0 and C<sub>g</sub>/C<sub>a</sub>=1.5.

Replace paragraph [0308] with:

The ozonizers 91, 92, 94 and 95 shown in Table 1 are all cylindrical multi-tube type ozonizers as described with FIG. 10, where the floating electrostatic capacity C<sub>p</sub>, which is parallel to the load, is so small and negligible, and the values of ~~C<sub>a</sub>/C<sub>p</sub> C<sub>p</sub>/C<sub>g</sub>~~ are shown as zero in Table 1. However, the ozonizer 93 has a peculiar structure and ~~C<sub>a</sub>/C<sub>p</sub>C<sub>p</sub>/C<sub>g</sub>~~ =0.63.

Replace paragraph [0390] with:

As shown in FIG. 31, inverter-connected IGBTs 11 and 21 and IGBTs 31 and ~~42~~ 41 are provided between the main power-supply lines (bus) P and N, and the output nodes of these sets of IGBTs are connected respectively to the reactor FL and an electrode of the ozonizer 1.

Replace paragraph [0391] with:

Also, IGBTs 12, 22, 32 and 42 are connected in parallel respectively with the IGBTs 11, 21, 31 and ~~42~~ 41.